



Small and strongly. The same tri level trencher with low dead weight for small soil contamination. With the Tilt mechanism can be adjust lateral downward gradient to 15°. The control platform is rotatable. The excavation can be ejected left or right, or be shipped directly with a reciprocally insertable conveyor. With an additional filling

judges milling and filling with gravel are possible in only one processing step. For direct cable and tubing introduction the GM1 all wheel can be equipped with further accessories. Beyond that the GM 1 can be equipped also with dual tire.

Individual equipment on request.

GM 1 (4WD)

Diekstraße 59, D-49809 Lingen
Tel. +4959176314, Fax +4959176547
info@Lingener-Baumaschinen.de
www.Lingener-Baumaschinen.de



Standard:

- ▶ Bank adjustment over hydraulic cylinders
- ▶ Rotatable operator platform with comfort seat
- ▶ Hydraulic steering
- ▶ Specially broad tires with fine lug tread
- ▶ Conveyor for the lateral ground ejection

Accessories:

- ▶ Cabine with heating and air conditioning system
- ▶ Filling snail aggregate with hydraulic drive
- ▶ 70 mm drainage slot equipment for sports field construction
- ▶ Filling judges for immediate filling after milling
- ▶ Shipping conveyor
- ▶ Laser price increase
- ▶ Cutter, mixture and chisel chains
- ▶ Hasp for drainage pipes
- ▶ Dual tires



Technical data:

Length: 4.400 mm
Height: 1.600 mm
Width: 1.310 mm

Weight:
approx. 1.960 kg

Widths:
70 - 300 mm

Depths:
600 - 1.400 mm

Drive:
3-Zyl. Diesengine
23 kW / 31,5 HP
4 wheel drive

