

# TRENCHER ATTACHMENT



**Economically and strongly.** The GM 1-AS is a cultivation trencher for the assembly at tractors with three point admission at the tail. It is ideal for the cable, tubing and drainage pipe installation. Particularly favorable is the small dead weight of the trencher, so that the trencher can be operated also at very small tractors. For an optimum at achievement the GM 1-AS can be equipped with various

cutter booms (600-1200 mm) and trench widths (70-300 mm). Over the change of the chain can be provided small drainage with 70 mm. The GM 1-AS is propelled over a power-takeoff. The excavation of the material is on the right and left side with two snails.

Individual equipment on request.

## GM 1-AS

Diekstraße 59, D-49809 Lingen  
Tel. +4959176314, Fax +4959176547  
info@Lingener-Baumaschinen.de  
www.Lingener-Baumaschinen.de



### Technical data:

Weight:  
approx. 600 kg

Widths:  
70 - 300 mm

Depths:  
600 - 1.200 mm

Trench chain drive:  
mechanically over  
power-takeoff

PTO speed:  
1.000 rpm

### Accessories:

- ▶ Sole circular scrapers with adjustment of the trench depths on request hydraulically
- ▶ Laser system (manual or automatic)
- ▶ Pipe drums and lying system
- ▶ Cutter, chisel and mixtured chains
- ▶ Hasp for drainage pipes

