



More flexibility at the excavator. The cultivation trencher GM 140 H (2 Cutter-Boom) is a high performance, economic trench, which are conceived particularly for the employment at hydraulic excavators. Installed at an excavator arm they offer the advantage to achieve and over obstacles away to work be able a large action field.

Working during driving is laterally, parallel facing forward, likewise possible. So those are often cultivation trench an ideal alternative to the self-propelled trenchers. Are optionally available among other things different trench bars, tubing moving pits and cable role owner in various remarks.

GM 140 H

Diekstraße 59, D-49809 Lingen
 Tel. +4959176314, Fax +4959176547
 info@Lingener-Baumaschinen.de
 www.Lingener-Baumaschinen.de



Practically and robust.

These model is available with differently long trench bars. The GMA series trench the grave as narrow as possible, which saves costs during the re-establishment of the grave. Steplessly adjustable depth control can be made manually or by a laser price increase. The back filling is facilitated, by or two additionally mountable snails the trench out ground to or two sides placing.



Technical data:

Weight:
 approx. 2.800 kg
 depending equipment

One-bar system
 Width:
 125 - 400 mm

Two-bar system
 Width:
 500 + 600 mm

Depths:
 600 - 1.500 mm

Millining chain drive:
 hydraulically

