



Achievement and flexibility. High performance 4-Zylinder trencher for many application type. The GM 4 all wheel has electrically hydraulic valves. So that the driver stand can be displaced on the left side of the machine (directly looks into the trench). The machine can be equipped additionally with a filling judges in order to settle a milling and a

filling with gravel in a rocessing step. Lateral downward gradient can be balanced to 12° inclination over the hydraulic Tilt mechanism. The excavation can be ejected reciprocally, to the right or left. Over an additional conveyor also direct shipping is possible. Individual equipments on request.

GM 4 (4WD)

Diekstraße 59, D-49809 Lingen
Tel. +4959176314, Fax +4959176547
info@Lingener-Baumaschinen.de
www.Lingener-Baumaschinen.de



Technical data:
(depends of the boom)

Length: 5.700 mm
Height: 2.300 mm
Width: 1.800 mm

Weight:
approx. 3.290 kg

Widths:
70 - 400 mm
Depths:
600 - 1.500 mm
(3.000 mm)

Drive:
4-Zyl. Dieselenigne
63 kW / 85,7 HP
4 wheel drive

Standard:

- ▶ Bank adjustment over hydraulic cylinders
- ▶ Shift-cash driver stand forward left
- ▶ Hydraulic steering element
- ▶ Specially broad tires with fine profile/dual tires
- ▶ Conveyor for the lateral ground ejection
- ▶ Hydrostatic all-wheel drive

Accessories:

- ▶ Cabin with heating and air conditioning system
- ▶ Vibration cable plow
- ▶ Filling snail aggregate with hydraulic propelled
- ▶ 70 mm of drainage slot equipment for sports field construction
- ▶ Filling judges for immediate filling after milling
- ▶ Conveyor
- ▶ Laser system for depths adjustment
- ▶ Cutter, mixture and chisel chains
- ▶ Hasp for drainage pipes
- ▶ Dual tires

