



The GM 4 is also available with crawler-type vehicle drive. Ideally for working on hard-to-travel and stony reason, whereby the fall of the chassis adjusts also surface irregularities. The GM 4 crawler-type vehicle is likewise propelled by a 4-Zylinder Diesel. It is optionally available with guiding roles for the direct cable and tubing introduction. The excavation can be ejected reciprocally to the

right or left and be shipped directly over an additional conveyor. The Tilt mechanism adjusts lateral downward gradient to 12° inclination hydraulically. The driver stand is forward on the left of shiftable, with which a direct view is possible on the milling chain and the grave.

Individual equipments on request.

## GM 4 Crawler

Diekstraße 59, D-49809 Lingen  
Tel. +4959176314, Fax +4959176547  
info@Lingener-Baumaschinen.de  
www.Lingener-Baumaschinen.de



### Standard

- ▶ Bank adjustment over hydraulic cylinders
- ▶ Shift-cash driver stand forward left
- ▶ Onepoti steering element
- ▶ Conveyor for the lateral ground ejection
- ▶ Fullhydrostatic drives

### Accessories:

- ▶ Cabin with heating and air conditioning system
- ▶ Vibration cable plow
- ▶ Filling snail aggregate with hydraulic drive
- ▶ 70 mm of drainage slot equipment for sports field construction
- ▶ Filling judges for immediate filling after milling
- ▶ Conveyor
- ▶ Laser system for depths adjustment
- ▶ Cutter, mixture and chisel chains
- ▶ Hasp for drainage pipes



**Technical data:**  
(depends of the boom)

Length: 5.700 mm  
Height: 2.300 mm  
Width: 1.800 mm

Weight:  
approx. 4.500 kg

Widths:  
70 - 400 mm  
Depths:  
600 - 1.500 mm  
Optionally  
up to 3.000mm

Drive:  
4-Zyl. Dieselenigne  
63 kW / 85,7 HP

